

RTD Motor/Generator Style Class 303

Stator Rtd
TRIMMABLE, REAR EXIT, LAMINATED

303 Stator Rtd, Trimmable, Rear Exit, Laminated							
303	Code		Classification				
	F		Class F, 155°C(311°F) Max., Epoxy glass, 3000 Volts Dielectric				
	Code		Accuracy Options				
	P2C		Platinum, 100 Ohm, +/- .5% at 0°C, .00385 temperature coefficient				
	C1D		Copper, 10 Ohm, +/- .2% at 25°C, .00427 temperature coefficient				
	Code		Element Configuration				
	3		Three wire single (color code: red/white(2))				
	Code		'A' Length				
	12		12" Overall length, 5.75" Sensitive length, 6.5" to 12" Usable length				
	18		18" Overall length, 9" Sensitive length, 10.5" to 18" Usable length				
	36		36" Overall length, 19.25" Sensitive length, 20.5" to 36" Usable length				
	Code		'B' Width				
	3		.260"				
	4		.305"				
5		.344"					
6		.455"					
7		.500"					
8		.625"					
Code		Material Thickness					
A		.030"					
B		.050"					
C		.078"					
303						Enter Part Number Here	
303	F	P2C	3	12	5	A	Example Part Number

